

Spec/Data

PF45

Polyester Fabric

Product Information

Adurel PF45 is a flat low profile fabric for use in the deck systems.

Recommended Uses

PF45 is used to increase tensile and add strength to moving joints where a flat profile is desired. Used primarily in decking applications.

Adurel PF45 can be used with:

A606	A707
A808	U5500
AC5000	U3300
U8800T	U7700
PC750	

Ordering Information

Packaging:

<u>Roll Size</u>	<u>Weight</u>	<u>Class</u>
6" x 300'	5 lbs.	65
4" x 300'	4 lbs.	65

D.O.T. Shipping Information: Nonhazardous, Nonflammable

HMIS: Health 1, Flammability 1, Reactivity 0, Protection B

Performance Characteristics

Property	ASTM	Result
Breaking Strength	D 1668 Type 1	45 x 40 lbs. / in. (avg.)
Construction		Stitch / Spun-bond
Gauge		7 cpi
Weight		2.3 oz. / sq. yard \pm 10%
Width		Variable / Per Customer Request

Application Information

Procedures

Apply base coat of desired Adurel material onto substrate at approximately 1 gallons per 100 sq. ft. Set polyester liner in wet material leaving no wrinkles. Apply saturation layer over polyester at 1.5 gallons per 100 sq. ft. Back-brush to remove wrinkles and trapped air.

Published technical data and instructions are subject to change without notice. Contact your Adurel representative for additional technical data and instructions.

Manufactured by

Adurel International, Inc.

820 Water St.

Racine, WI 53403

800.860.5834 262.632.3446 Fax

adurel.com