Material Safety Data Sheet

Emergency Phone: (PERS 800-633-8253 domestic 801-629-0667 International)

I. Chemical Product And Company Data

PRODUCT: ADUREL Nytro Accelerator

CHEMICALFAMILY: Amine

REVISION DATE: 10/23/04

MANUFACTURER: Adurel International Inc

820 Water St. Racine WI 53403 800-860-5834 fx 262-632-3446 Personal Protection **H**

2

0

Health

Flammability

Reactivity

II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

EXPOSURE LIMITS

HAZARDOUS INGREDIENTS CAS NO TLV STEL PEL CONTENT

Diethyltoluenediamine 68479-98-1 N/E N/E N/E 97.5%

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

None

III. Hazards Identification

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

Skin Contact: May cause irritation to the skin and is expected to be absorbed.

Eyes: May cause irritation to the eyes.

Inhalation Minimal inhalation hazard with industrial use, although it is expected that absorption will

occur through the lungs.

Ingestion: Not expected to be a relevant route of exposure although it may cause permanent

damage to the mouth throat and stomach.

IV. First Aid Measures

<u>Inhalation</u> Remove victim from exposure. If difficulty with breathing, administer oxygen and

seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye

lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If

irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs

spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do

not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 0

<u>Flash Point:</u> > 135 °C (275 °F) <u>Method</u>: T. C.C. <u>General Hazard:</u> Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

<u>Limits of Flammability</u>
<u>Extinguishing Media</u>

LEL: Not Available
UEL: Not Available
Carbon Dioxide, foam, dry chemical, water spray or fog.

Special Fire & Unusual Hazards Move containers from area if it can be done without risk. Cool fire-

exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing

apparatus and full protective gear.

VI. Accidental Release Measures

<u>Action To Take For Spills/ Leaks:</u> Avoid contact with skin or eyes. Ventilate area, eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

<u>Waste Disposal Method:</u> Handle disposal of waste material in manner which complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Average Shelf Life: Refer to Product Data Sheet Special Instructions Store away from heat.

VIII. Exposure Controls / Personal Protection

<u>Ventilation:</u> Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

<u>Personal Protection Equipment:</u> Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C): 308 Water/Oil Distribution N/A

Coefficient:

Percent Volatile: N/A Solubility in Water: 1.0 % Freezing Point (°C): Specific Gravity @20° C 1.02 N/A Vapor Pressure @ 126° C 0.97 mm Hg :Ha N/A **Evaporation Rate:** Vapor Density 6.2 (air = 1)N/A Odor Threshold: Pungent N/A Odor:

Appearance: Light brown liquid

N/A = Not Available N/D=NOT Determined Ca. = Approximate

X. Stability And Reactivity

HMIS Hazard Rating No. 0

<u>Stability</u> Stable

<u>Incompatibility:</u> Strong acids and oxidizers.

<u>Hazardous Decomposition Products</u> Oxides of carbon, nitrogen and sulfur.

<u>Conditions To Avoid</u> High heat and humidity.

XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes, and ingestion.

Effects Of Overexposure

Inhalation: Minimal inhalation hazard with industrial use

<u>Eyes:</u> May cause irritation.

Skin Contact: May cause irritation and sensitization.

<u>Ingestion:</u> May cause permanent damage to the mouth throat and stomach.

Chronic: This product does not contain chemicals considered to be carcinogenic by

NTP, IRAC, ACGIH, OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in manner which complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATON

DOT Proper Shipping Name NOT REGULATED

DOT Hazard Class

DOT I.D Number Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard Hazardous

(29 CFR 1910.1200)

CERCLA/ Super fund (40 CFR 117,302) N/A

SARA Extremely Hazardous Substances

(40 CFR 355)

SARA Hazard Categories (40 CFR 370) Health : Delayed (chronic)

Physical: None

SARA Toxic Chemicals (40 CFR 372) None

Inventory Status The chemicals in this product are listed on the US

N/A

TSCA Chemical Substance Inventory and the

Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CAN NOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.